

**CAT IV****300 V****IP65**

Basic measurements of earthing systems and continuity of connections

Measurement methods

- **3-pole method** – measurement of earthing systems using auxiliary probes
- **2-pole method** – simplified measurement of resistance-to-earth
- **Resistance of earth connection and equipotential bonding** measured using current ≥ 200 mA with auto-zero function – meets the requirements of EN 61557-4

Additional features

- Measurement of resistance of auxiliary electrodes R_s and R_h
- Measurement of interference voltage
- Selection of maximum measuring voltage (25 V and 50 V)
- Auto-zero function for the resistance of measurement leads (R_{CONT} zero)

Application

MRU-21 is designed as a reliable measuring instrument, which is both technically advanced and easy to use. It is suitable for tests in industrial plants and in companies providing electrical measurement services. MRU-21 allows user to test individual earth electrodes and systems with multiple earthing electrodes.



Capabilities

Large and easy to read display shows the resistance values and supporting information in all weather conditions. Additional warnings inform the user about irregularities during the measurement.

Housing with IP54 rating ensures safety in difficult weather conditions and protect the device against splashes.

The results can be saved to the device's memory. It is divided into **10 banks of 99 cells**, each corresponding to one measurement. These results can be easily transferred to the **Sonel Reader** software for archiving or subsequent analysis and research.


Technical specifications

Measurement functions	Measurement range	Display range	Resolution	Accuracy ±(% m.v. + digits)
Interference voltage	0 V...100 V	0 V...100 V	1 V	±(2% m.v. + 3 digits)
Resistance of earth connection and equipotential bonding	0.13 Ω...199 Ω acc. to EN 61557-4	0.00 Ω...199 Ω	from 0.01 Ω	±(2% m.v. + 3 digits)
Earth resistance				
2-pole method	0.00 Ω...1.99 kΩ	0.00 Ω...1.99 kΩ	from 0.01 Ω	from ±(2% m.v. + 3 digits)
3-pole method	0.50 Ω...1.99 kΩ acc. to EN 61557-5	0.00 Ω...1.99 kΩ	from 0.01 Ω	±(2% m.v. + 3 digits)
auxiliary electrodes resistance	0 Ω...50.0 kΩ	0 Ω...50.0 kΩ	from 1 Ω	±(5% ($R_E+R_H+R_S$) + 3 digits)
Safety and work conditions				
Measuring category according to EN 61010				III 600 V / IV 300 V
Ingress protection				IP54
Type of insulation according to EN 61010-1 and IEC 61557				double
Dimensions				288 x 223 x 75 mm 11.3" x 8.8" x 3.0"
Weight				ca. 1.4 kg ca. 3.1 lbs
Operating temperature				-10...+55°C 14...131°F
Storage temperature				-20...+70°C -2...+157°F
Humidity				20...90%
Nominal temperature				23 ± 2°C 73.4°F ± 3.6°F
Reference humidity				40%...60%
Memory and communication				
Memory of measurement results				990 results
Data transmission				USB
Other information				
Quality standard – development, design and production				ISO 9001
The product meets the EMC (emission for industrial environment) requirements according to standards				EN 61326-1 EN 61326-2-2

Standard accessories

	<p>Test lead 15 m on a reel, banana plugs, blue</p> <p>WAPRZ015BUBBSZ</p>		<p>Test lead 1.2 m (banana plugs) blue</p> <p>WAPRZ1X2BUBB</p>		<p>Crocodile clip 1 kV 20 A blue</p> <p>WAKROBU20K02</p>
	<p>Test lead 30 m for earth resistance measurements on a reel, red</p> <p>WAPRZ030REBBSZ</p>		<p>Test lead 2.2 m (banana plugs) black</p> <p>WAPRZ2X2BLBB</p>		<p>Crocodile clip 1 kV 20 A black</p> <p>WAKROBL20K01</p>
	<p>2 x earth contact test probe (30 cm)</p> <p>WASONG30</p>		<p>USB cable</p> <p>WAPRZUSB</p>		<p>Battery pack 4xLR14</p> <p>WAPOJ1</p>
	<p>L-4 carrying case</p> <p>WAFUTL4</p>		<p>Hanging straps</p> <p>WAPOZSZEKPL</p>		<ul style="list-style-type: none">• 4 x R14 alkaline battery• Factory calibration certificate

Optional accessories

	<p>Test lead on a reel red 75 m / 100 m / 200 m</p> <p>WAPRZ075REBBSZ WAPRZ100REBBSZ WAPRZ200REBBSZ</p>		<p>Test lead on a reel blue 75 m / 100 m / 200 m</p> <p>WAPRZ075BUBBSZ WAPRZ100BUBBSZ WAPRZ200BUBBSZ</p>		<p>Test lead on a reel yellow 75 m / 100 m / 200 m</p> <p>WAPRZ075YEBBSZ WAPRZ100YEBBSZ WAPRZ200YEBBSZ</p>
	<p>Test lead 25 / 30 m on a reel, banana plugs, red</p> <p>WAPRZ025REBBSZ WAPRZ030REBBSZ</p>		<p>Test lead 15 / 25 m on a reel, banana plugs, blue</p> <p>WAPRZ015BUBBSZ WAPRZ025BUBBSZ</p>		<p>Test lead 50 m for earth resistance measurements (ba- nana plugs) yellow</p> <p>WAPRZ050YEBBSZ</p>
	<p>Pin probe 1 kV (banana socket) black / red / blue / yellow</p> <p>WASONBUOGB1 WASONREOGB1 WASONBLOGB1 WASONYEGB1</p>		<p>Test lead 1.2 m (banana plugs) black / red / blue / yellow</p> <p>WAPRZ1X2BLBB WAPRZ1X2REBB WAPRZ1X2BUBB WAPRZ1X2YEBB</p>		<p>Crocodile clip 1 kV 20 A red / blue / yellow</p> <p>WAKRORE20K02 WAKROBU20K02 WAKROYE20K02</p>
	<p>Cramp with banana socket</p> <p>WAZACIMA1</p>		<p>Earth contact test probe 25 cm / 80 cm</p> <p>WASONG25 WASONG80V2</p>		<p>L-3 carrying case (for 80 cm test probes)</p> <p>WAFUTL3</p>
	<p>Test wire reel</p> <p>WAPOZSZP1</p>		<p>Calibration certificate with accreditation</p>		